



- Manufactured in the UK
- Unbeatable Recovery & Efficiency
- 316 Stainless Steel Frame & Pipework
- Fully Programmable
- 2 Line LED Display
- Customisable Colour and Logo
- Stainless Solenoids and Control Valves
- Stainless Membrane Housing and End Caps
- Stainless Inlet Filter
- Fully Factory Tested and Set Up to your spec
- IP65 Rated
- Compatible with One Flow Technology

Industrial Water Equipment Ltd

RAVENSTOR ROAD, WIRKSWORTH, DERBYSHIRE, DE4 4FY

+44 (0) 1629 363311

MODEL PROMAX 8		4300	5400	7000	8000	9500	12000
Permeate flow rate	l/h	4,300	5,400	7,000	8,000	9,500	12,000
Min. salt rejection	%	97	97	97	97	97	97
Recovery	%	75-80	75-80	75-80	75-80	75-80	75-80
Operating pressure	bar	13.5	13.0	13.5	13.0	13.5	12.5
Membrane element / number		8040/3	8040/4	8040/5	8040/6	8040/7	8040/9
Voltage	V/Hz	3x400/50	3x400/50	3x400/50	3x400/50	3x400/50	3x400/50
Motor power	kW	5.5	5.5	7.5	11	11	11
Pre-fusing	A	32	32	32	32	32	32
Feedwater connection	BSP	2"	2"	2"	2"	2"	2"
Concentrate connection	Plain Union	2"	2"	2"	2"	2"	2"
Permeate connection	Plain Union	2"	2"	2"	2"	2"	2"
Conductivity range	µS/cm	1-200	1-200	1-200	1-200	1-200	1-200
Min. / max. feed water pressure	bar	2/7	2/7	2/7	2/7	2/7	2/7
Min. / max. feed water temp	°C	5/35	5/35	5/35	5/35	5/35	5/35
Max. ambient temperature	°C	45	45	45	45	45	45
pH		3-12	3-12	3-12	3-12	3-12	3-12
Height	mm	1800	1800	1800	1800	1800	1800
Width	mm	2600	2600	2600	2600	2600	2600
Depth	mm	850	850	850	850	850	850
Weight approx	ca. kg	500	550	650	750	850	950