



- Manufactured in the UK
- Unbeatable Recovery & Efficiency
- 316 Stainless Steel Frame & Pipework
- Mounted on a 1000 Ltr IBC
- Customisable Colour and Logo
- Stainless Solenoids and Control Valves
- Fully Programmable
- Fully Factory Tested and Set Up to your spec
- IP65 Rated
- High Level Switch in IBC Included

Industrial Water Equipment Ltd

44 NEW STREET MATLOCK DERBYSHIRE DE4 3DN

+44 (0) 1629 55839

MODEL		COMPACT 150 IBC
Permeate flow rate	l/h	150
Min. salt rejection	%	95
Recovery	%	Up to 80
Operating pressure	bar	10.0
Membrane element / number		4021/1
Voltage	V/Hz	230/50
Motor power	kW	0.4
Pre-fusing	A	2.5
Feedwater connection	R	¾" AG
Permeate/concentrate connection	DN	10
Conductivity range	µS/cm	1 – 99
Min. / max. feed water pressure	bar	3 / 6
Min. / max. feed water temp	°C	5 / 35
Max. ambient temperature	°C	40
pH		3 – 11
Height	mm	1600
Width	mm	1200
Depth	mm	1000
Weight approx	ca. kg	480
Code no		