



- Manufactured in the UK
- Unbeatable Recovery & Efficiency
- 316 Stainless Steel Frame & Pipework
- Fully Programmable
- 2 Line LED Display
- Stainless Solenoids and Control Valves
- Stainless Inlet Filter
- Customisable Colour and Logo
- Fully Factory Tested and Set Up to your spec
- IP65 Rated

Industrial Water Equipment Ltd

RAVENSTOR ROAD, WIRKSWORTH, DERBYSHIRE, DE4 4FY

+44 (0) 1629 363311

| MODEL COMPACT                   |        | 150      |
|---------------------------------|--------|----------|
| Permeate flow rate              | l/h    | 150      |
| Min. salt rejection             | %      | 95       |
| Recovery                        | %      | Up to 80 |
| Operating pressure              | bar    | 10.0     |
| Membrane element / number       |        | 4021/1   |
| Voltage                         | V/Hz   | 230/50   |
| Motor power                     | kW     | 0.4      |
| Pre-fusing                      | A      | 13       |
| Feedwater connection            | BSP    | ¾"       |
| Permeate connection             | BSP    | ½"       |
| Concentrate connection          | BSP    | ½"       |
| Conductivity range              | µS/cm  | 1 – 99   |
| Min. / max. feed water pressure | bar    | 3 / 6    |
| Min. / max. feed water temp     | °C     | 5 / 35   |
| Max. ambient temperature        | °C     | 40       |
| pH                              |        | 3 – 11   |
| Height                          | mm     | 370      |
| Width                           | mm     | 800      |
| Depth                           | mm     | 370      |
| Weight approx                   | ca. kg | 31       |
| Code no                         |        |          |